

Technical Data Sheet

Product Number R2-8250-5
 Product Name HELIOCOLOR-W RED 122
 Color-Index PR 122

Issue Date 25.07.2023

Composition

Pigment content [%] 20,000
 solid content [%] 94,349
 plasticiser [%] 75,100

Specification

EP07

Specification	min. Level	max. Level	Plan Level	Text	Test method
Standard lot no.				F152185	
STD-BATCH delta L	-0,8000	0,8000			PM-0020
STD-BATCH delta a	-0,8000	0,8000			PM-0020
STD-BATCH delta b	-0,8000	0,8000			PM-0020
STD-BATCH delta E		1,0000			PM-0020
STD-BATCH delta CS	97,5000	102,5000			PM-0020
Fineness of grain [µm]		20,0			PM-0012

Fastnesses of the basic pigments in the pigment preparation

Lightfastness (Full shade / Reduction) 7-8 / 7-8
 Wether Fastness (Full shade / Reduction) 4 / 4-5
 Alkali Resistance 5
 Acid Resistance 5
 Temperature Resistance [°C] 200

Tariff of duties no.

32129000

Origin of goods

Germany

Inventory

EC-No	Yes
TSCA-USA	Yes
AICS-Australien	Yes
DSL/NDSL-Kanada	Yes
PICCS-Philippinen	Yes
MITI/ENCS-Japan	Yes
ECL-Korea	Yes
TCSI-Taiwan	Yes
NZIOC-New Zealand	Yes
IECSC-China	Yes
Schweiz (EC-No/EINECS)	Yes

Technical Data Sheet

Product Number	R2-8250-5		
Product Name	HELIOCOLOR-W RED 122		
Color-Index	PR 122	Issue Date	25.07.2023

Important Notice

Always test the preparation for compatibility and suitability in the intended application system.

Suitable pigments should be specifically selected for each application system.

Colour index data refers to the basic pigment form.

Values provided on this data sheet are typical and may vary as the products are standardised according to colour strength.

The data provided herein is based on our current knowledge but does not guarantee any particular property.

It is the responsibility of the end user to ensure that products utilising these materials meet and comply with all relevant laws and regulations.

Stir well before use!

Close the container after use!